

INDEX

- [1. Signature](#)
- [2. Balance request](#)
- [3. Lists request](#)
- [4. Request for senders list](#)
- [5. Request for numbers from list](#)
- [6. Status request](#)
- [7. SMS sending](#)
- [8. Search in the blacklist](#)
- [9. Adding a number to the blacklist](#)
- [10. Request for templates list](#)
- [11. Adding a template](#)
- [12. Deleting a template](#)
- [13. General statistics for a month](#)
- [14. HLR request](#)
- [15. Statistics of HLR requests](#)
- [16. Mobile operator query](#)
- [17. Request for incoming SMS](#)
- [18. Request for prices](#)
- [19. Error codes](#)

1. Signature

Signature

All requests should contain the required parameter **timestamp** - that in its turn should be included in a signature and is valid for 86400 seconds.

You can request for timestamp by the address: <https://go.intistele.com/external/get/timestamp.php>

Signature (signature parameter) - md5 hash, which is formed the following way:

You should sort all the parameters alphabetically in a string and add at the end of the string an API key. The sequence of parameters in the request is not important.

Example for the

request <https://go.intistele.com/external/get/balance.php?login=testuser&signature=444ea37c444358d53a928e7db26b4f89×tamp=1480266800>

thus, the signature consists of the following parameters login, timestamp and API key:
444ea37c444358d53a928e7db26b4f89

A simple example of making a signature in PHP

The ready example of the simplest function of making a signature in PHP

```
function Signature( $params, $api_key )
{
    ksort( $params );
    reset( $params );

    return md5( implode( $params ) . $api_key );
}
```

There is a set of parameters

```
$params = array(
    'timestamp' => '1480266800',
    'login'     => 'YourLogin',
    'phone'    => '17076295568',
    'sender'   => 'smstest'
    'text'     => 'Long text'
);
```

You should sort it alphabetically

```
ksort( $params );
reset( $params );
```

As a result you will see

```
Array
(
    [login] => YourLogin
```

```
[phone] => 17076295568
[sender] => smstest
[text] => Long text
[timestamp] => 1480266800
)
```

Convert the result to a string

```
implode( $params );
```

As a result you will see

```
YourLogin17076295568smstestLong text1480266800
```

Add your API key at the end of the string - 75a55c70c495a0ae8a7c512166b2bc6d7c9cc153

```
YourLogin17076295568smstestLong text148026680075a55c70c495a0ae8a7c512166b2bc6d7c9cc153
```

Convert the result to md5 hash

```
md5( 'YourLogin17076295568smstestLong text148026680075a55c70c495a0ae8a7c512166b2bc6d7c9cc153' );
```

You will get a valid signature as a result that you should substitute in the appropriate parameter of the request

```
12a574ae79253d622293df7321d9cd11
```

i.e. the final request will be:

```
https://go.intistele.com/external/get/PAGE.php?login=YourLogin&timestamp=1480266800&phone=17076295568&text=Long%20text&signature=12a574ae79253d622293df7321d9cd11
```

2. Balance request

Balance request

Server address for requests: <https://go.intistele.com/external/get/balance.php>

It is necessary to specify in the request three obligatory parameters **login**, **signature** and **timestamp**

login - Your login

signature - signature

timestamp - UTC Timestamp

Request example:

```
https://go.intistele.com/external/get/balance.php?login=testuser&signature=edf4f88f25cf7a4f30a1ad0283adfe1b&timestamp=1480266868
```

There is a fourth optional parameter **return** that can be one of two values: json, xml

Request example:

```
https://go.intistele.com/external/get/balance.php?login=testuser&signature=73dbb518262dd07d9823b5ace8c92d39&timestamp=1480266868&return=json
```

Response example:

```
{"money" : "69573.1", "currency" : "RUR"}
```

Request example:

```
https://go.intistele.com/external/get/balance.php?login=testuser&signature=063e664f2365d4b8b64377d7d3dfffa83&timestamp=1480266868&return=xml
```

Response example:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
  <money>69573.1</money>
  <currency>RUR</currency>
</response>
```

3. Lists request

Lists request

Server address for requests: <https://go.intistele.com/external/get/base.php>

It is necessary to specify in the request three obligatory parameters **login**, **signature** and **timestamp**

login - Your login

signature - signature

timestamp - UTC Timestamp

Request example:

```
https://go.intistele.com/external/get/base.php?login=testuser&signature=8a8d9030d140861aac7b6eae32ebfc97&timestamp=1480266959
```

There is a fourth optional parameter **return** that can be one of two values: json, xml

Request example:

```
https://go.intistele.com/external/get/base.php?login=testuser&signature=1e7a0627d17d4d9d20486ecb701a7b15&return=json&timestamp=1480266959
```

Response example:

```
{
  "125448": {
    "name": "All qualified leads",
    "time_birth": "12:00:00",
    "day_before": "0",
    "local_time": "1",
    "birth_sender": "",
    "birth_text": "",
    "on_birth": "0",
    "count": "3618",
    "pages": "37"
  },
  "125452": {
    "name": "Valuable clients",
    "time_birth": "12:00:00",
    "day_before": "0",
    "local_time": "1",
    "birth_sender": "",
    "birth_text": "",
    "on_birth": "0",
    "count": "2255",
    "pages": "23"
  },
  "125453": {
    "name": "Partners",
    "time_birth": "12:00:00",
    "day_before": "0",
    "local_time": "1",
    "birth_sender": "",
    "birth_text": "",
    "on_birth": "0",
    "count": "2266",
    "pages": "23"
  },
  "125454": {
    "name": "All leads and clients",
    "time_birth": "12:00:00",
    "day_before": "0",
    "local_time": "0",
    "birth_sender": "Stok&Sekond",
    "birth_text": "",
    "on_birth": "1",
    "count": "11537",
    "pages": "116"
  }
}
```

Request example:

```
https://go.intistele.com/external/get/base.php?login=testuser&signature=089bd33d8d01c58304f00ea321fead28&return=xml&timestamp=1480266959
```

Response example:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
<bases>
<base base="125448" name="All qualified leads" time_birth="12:00:00" day_before="0"
    local_time="1" birth_sender="" birth_text=""
    on_birth="0" count="3618" pages="37" />
<base base="125452" name="Valuable clients" time_birth="12:00:00" day_before="0"
    local_time="1" birth_sender="" birth_text=""
```

```
        on_birth="0" count="2255" pages="23" />
<base base="125453" name="Partners" time_birth="12:00:00" day_before="0"
    local_time="1" birth_sender="" birth_text=""
    on_birth="0" count="2266" pages="23" />
<base base="125454" name="All leads and clients" time_birth="12:00:00" day_before=
"0"
    local_time="0" birth_sender="Stok&Sekond" birth_text=""
    on_birth="1" count="11537" pages="116" /></bases>
</response>
```

4. Request for senders list

Request for senders list

Server address for requests: <https://go.intistele.com/external/get/senders.php>

It is necessary to specify in the request three obligatory parameters **login**, **signature**, **timestamp**

login - Your login

signature - signature

timestamp - UTC Timestamp

Request example:

```
https://go.intistele.com/external/get/senders.php?login=testuser&signature=f4848c9382c0a3ac187ea6ecb4747bf9&timestamp=1480266999
```

There is a fourth optional parameter **return** that can be one of two values: json, xml

Request example:

```
https://go.intistele.com/external/get/senders.php?login=testuser&signature=0a5f28cbba55a45b832000113a2f44da&return=json&timestamp=1480266999
```

Response example:

```
{"smstest": "completed", "smstest2": "completed"}
```

Request example:

```
https://go.intistele.com/external/get/senders.php?login=testuser&signature=2fd93c4aa3a9852ad6031a6a19941c98&return=xml&timestamp=1480266999
```

Response example:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
<senders>
<sender sender="smstest" state="completed" />
<sender sender="smstest2" state="completed" />
</senders>
</response>
```

5. Request for numbers from list

Request for numbers from list

Server address for requests: <https://go.intistele.com/external/get/phone.php>

It is necessary to specify in the request five obligatory parameters **login**, **signature**, **base**, **page**, **timestamp**

login - Your login
signature - signature
base - List ID
page - Page number
timestamp - UTCTimestamp

Request example:

```
https://go.intistele.com/external/get/phone.php?login=testuser&signature=4c8622f1d85f4913bd584094c2dc793d&base=125454&page=1&timestamp=1480267042
```

There is a sixth optional parameter **return** that can be one of two values: json, xml

Request example:

```
https://go.intistele.com/external/get/phone.php?login=testuser&signature=9d439a0ecbb1cbfcb3211754986f12bc&base=125454&page=1&return=json&timestamp=1480267042
```

Response example:

```
{
  "79687931116": {
    "name": "",
    "last_name": "",
    "middle_name": "",
    "date_birth": "0000-00-00",
    "male": "",
    "note1": "",
    "note2": "",
    "region": "",
    "operator": ""
  },
  "79874617237": {
    "name": "",
    "last_name": "",
    "middle_name": "",
    "date_birth": "0000-00-00",
    "male": "",
    "note1": "",
    "note2": "",
    "region": "",
    "operator": ""
  },
  "79871846995": {
    "name": "",
    "last_name": "",
    "middle_name": "",
    "date_birth": "0000-00-00",
    "male": "",
    "note1": "",
    "note2": "",
    "region": "",
    "operator": ""
  }
}
```

Request example:

```
https://go.intistele.com/external/get/phone.php?login=testuser&signature=66b5cc7d1b066056c0544e28208e6187&base=125454&page=1&return=xml&timestamp=1480267042
```

Response example:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
<phones>
<phone phone="7968793****" name="" last_name="" middle_name=""
      date_birth="0000-00-00" male="" note1=""
      note2="" region="" operator="" />
<phone phone="7987461****" name="" last_name="" middle_name=""
      date_birth="0000-00-00" male="" note1=""
```



```
        note2="" region="" operator="" />
<phone phone="7987184****" name="" last_name="" middle_name=""
        date_birth="0000-00-00" male="" note1=""
        note2="" region="" operator="" />
</phones>
</response>
```

6. Status request

Status request

Server address for requests: <https://go.intistele.com/external/get/status.php>

It is necessary to specify in the request four obligatory parameters **login**, **signature**, **state**, **timestamp**

login - Your login

signature signature

state - status ID. If you need statuses of several SMS, you should specify ID separated by commas.

timestamp - UTC Timestamp

Request example:

```
https://go.intistele.com/external/get/status.php?login=testuser&signature=32cbc987d9bf662b4838bd15ffa6c300&state=4091297100348873330001,4091297100348880230003&timestamp=1480267081
```

There is a fifth optional parameter **return** that can be one of two values: json, xml

Request example:

```
https://go.intistele.com/external/get/status.php?login=testuser&signature=fc440a6ce438aedb4e6eadb77cb1a232&state=4091297100348873330001,4091297100348880230003&return=json&timestamp=1409887191
```

Response example:

```
{ "4091297100348873330001" : "not_deliver", "4091297100348880230003" : "not_deliver" }
```

Request example:

```
https://go.intistele.com/external/get/status.php?login=testuser&signature=fc440a6ce438aedb4e6eadb77cb1a232&state=4091297100348873330001,4091297100348880230003&return=xml&timestamp=1409887191
```

Response example:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
<statuses>
<status id_sms="4091297100348873330001" status="not_deliver" />
<status id_sms="4091297100348880230003" status="not_deliver" />
</statuses>
</response>
```

7. SMS sending

SMS sending

Server address for requests: <https://go.intistele.com/external/get/send.php>

It is necessary to specify in the request six obligatory parameters **login**, **signature**, **phone**, **text**, **sender**, **timestamp**

login - Your login

signature - signature

phone - One or several numbers separated by commas (no more than 100 numbers in the request)

text - Text of SMS message

sender - Sender name (one of the approved in your account)

timestamp - UTC Timestamp

sendingTime - Example: 2014-05-30 14:06 (an optional parameter, it is used when it is necessary to schedule SMS messages)

Request example:

```
https://go.intistele.com/external/get/send.php?login=testuser&signature=99d9dc21c606b0b0e9faa1cb9e2014b3&phone=17076295568&text=%D0%A2%D0%B5%D1%81%D1%82%D0%BE%D0%B2%D0%BE%D0%B5+%D0%A1%D0%9C%D0%A1+%D1%81%D0%BE%D0%BE%D0%B1%D1%89%D0%B5%D0%BD%D0%B8%D0%B5+%22Test+SMS%22%21&sender=smstest&timestamp=1480267121
```

There is a seventh optional parameter **return** that can be one of two values: json, xml

Request example:

```
https://go.intistele.com/external/get/send.php?login=testuser&signature=5552e1bfc067c4321be7c42cb2f09628&phone=17076295568&text=Hello!&sender=smstest&return=json&timestamp=1409887191
```

Response example:

```
{"17076295568":{"error":"0", "id_sms":"4092112510348380960001", "cost":"0.5", "count_sms":"1"}}
```

Request example:

```
https://go.intistele.com/external/get/send.php?login=testuser&signature=5552e1bfc067c4321be7c42cb2f09628&phone=17076295568&text=Hello!&sender=smstest&return=xml&timestamp=1409887191
```

Response example:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
<phones>
<phone phone="17076295568" error="0" id_sms="4092113100349055700001" cost="0.5" count_sms="1" />
</phones>
```

```
</response>
```

8. Search in the blacklist

Search in the black list

Server address for requests: https://go.intistele.com/external/get/find_on_stop.php

It is necessary to specify in the request four obligatory parameters **login**, **signature**, **phone**, **timestamp**

login - Your login

signature - signature

phone - Required number

timestamp - UTC Timestamp

Request example:

```
https://go.intistele.com/external/get/find_on_stop.php?login=testuser&signature=66118f73481834efb077bdc4083f5fae&phone=17076295568&timestamp=1409887191
```

There is a fifth optional parameter **return** that can be one of two values: json, xml

Request example:

```
https://go.intistele.com/external/get/find_on_stop.php?login=testuser&signature=66118f73481834efb077bdc4083f5fae&phone=17076295568&return=json&timestamp=1409887191
```

Response example:

```
{"time_in" : "2014-08-29 11:07:43", "description" : "descr"}
```

Request example:

```
https://go.intistele.com/external/get/find_on_stop.php?login=testuser&signature=66118f73481834efb077bdc4083f5fae&phone=17076295568&return=xml&timestamp=1409887191
```

Response example:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
<time_in>2014-08-29 11:07:43</time_in>
<description>descr</description>
</response>
```

9. Adding a number to the blacklist

Adding a number to the stop list

Server address for requests: <https://go.intistele.com/external/get/add2stop.php>

It is necessary to specify in the request four obligatory parameters: **login**, **signature**, **phone**, **timestamp**

login - Your login

signature - signature

phone - Number to be added to the stop list

timestamp - UTC Timestamp

Request example:

```
https://go.intistele.com/external/get/add2stop.php?login=testuser&signature=66118f73481834efb077bdc4083f5fae&phone=17076295568&timestamp=1409887191
```

There is a fifth optional parameter **return** that can be one of two values: json, xml

Request example:

```
https://go.intistele.com/external/get/add2stop.php?login=testuser&signature=66118f73481834efb077bdc4083f5fae&phone=17076295568&timestamp=1409887191&return=json
```

Response example:

```
{"id" : "4419373"}
```

Request example:

```
https://go.intistele.com/external/get/add2stop.php?login=testuser&signature=66118f73481834efb077bdc4083f5fae&phone=17076295568&timestamp=1409887191&return=xml
```

Response example:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
<id>4419374</id>
</response>
```

10. Request for templates list

Request for templates list

Server address for requests: <https://go.intistele.com/external/get/template.php>

It is necessary to specify in the request three obligatory parameters **login**, **signature**, **timestamp**

login - Your login

signature - signature

Request example:

```
https://go.intistele.com/external/get/template.php?login=testuser&signature=b27f321d0b50d914ebbd01f754fe7af7&timestamp=1409887191
```

There is a fifth optional parameter **return** that can be one of two values: json, xml

Request example:

```
https://go.intistele.com/external/get/template.php?login=testuser&signature=b27f321d0b50d914ebbd01f754fe7af7&return=json&timestamp=1409887191
```

Response example:

```
{"test" : {"template":"text", "up_time":"2014-08-28 15:22:25"}, "test22" : {"template":"testtt 1321321231321", "up_time":"2014-08-28 15:39:07"}}
```

Request example:

```
https://go.intistele.com/external/get/template.php?login=testuser&signature=b27f321d0b50d914ebbd01f754fe7af7&return=xml&timestamp=1409887191
```

Response example:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
<templates>
<template name="test" template="text" up_time="2014-08-28 15:22:25" />
<template name="test22" template="testtt 1321321231321" up_time="2014-08-28 15:39:07" />
</templates>
</response>
```

11. Adding a template

Adding a template

Server address for requests: https://go.intistele.com/external/get/add_template.php

It is necessary to specify in the request five obligatory parameters: **login**, **signature**, **name**, **text**, **timestamp**

login - Your login

signature - signature

name - Template name

text - Template text

timestamp - UTC Timestamp

override - Example: 0 or 1 (an optional parameter; it is used for template editing, if the template you want to edit is found and the override parameter is 1, the template will be edited)

Request example:

```
https://go.intistele.com/external/get/add_template.php?login=testuser&signature=4b7ed75ac8d36a8f88244f4b2aa00b0e&name=test22&text=testtt 1321321231321&timestamp=1409887191
```

There is a sixth optional parameter **return** that can be one of two values: json, xml

Request example:

```
https://go.intistele.com/external/get/add_template.php?login=testuser&signature=4b7ed75ac8d36a8f88244f4b2aa00b0e&name=test22&text=testtt 1321321231321&timestamp=1409887191&return=json
```

Response example:

```
{"id" : "4419373"}
```

Request example:

```
https://go.intistele.com/external/get/add_template.php?login=testuser&signature=4b7ed75ac8d36a8f88244f4b2aa00b0e&name=test22&text=testtt 1321321231321&timestamp=1409887191&return=xml
```

Response example:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
<id>4419374</id>
</response>
```


12. Deleting a template

Deleting a template

Server address for requests: https://go.intistele.com/external/get/del_template.php

It is necessary to specify in the request four obligatory parameters: **login**, **signature**, **name**, **timestamp**

login - Your login
signature - signature
name - Template name
timestamp - UTC Timestamp

Request example:

```
https://go.intistele.com/external/get/del_template.php?login=testuser&signature=704978b600899672c512cfce90ee7459&name=test22&timestamp=1409887191
```

There is a fifth optional parameter **return** that can be one of two values: json, xml

Request example:

```
https://go.intistele.com/external/get/del_template.php?login=testuser&signature=704978b600899672c512cfce90ee7459&name=test22&timestamp=1409887191&return=json
```

Response example:

```
{"result" : "deleted"}
```

Request example:

```
https://go.intistele.com/external/get/del_template.php?login=testuser&signature=704978b600899672c512cfce90ee7459&name=test22&timestamp=1409887191&return=xml
```

Response example:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
<result>deleted</result>
</response>
```

13. General statistics for a month

General statistics for a month by days

Server address for requests: https://go.intistele.com/external/get/stat_by_month.php

It is necessary to specify in the request four obligatory parameters **login**, **signature**, **month**, **timestamp**

login - Your login

signature - signature

month - Year and month in the format YYYY-MM

timestamp - UTC Timestamp

Request example:

```
https://go.intistele.com/external/get/stat_by_month.php?login=testuser&signature=a1ad6728c8cba0eb3841cb5d6de19b6e&month=2016-11&timestamp=1480267314
```

There is a fifth optional parameter **return** that can be one of three values: array, json, xml

Request example:

```
https://go.intistele.com/external/get/stat_by_month.php?login=testuser&signature=809673402e973567ef892651a9714bf9&month=2014-08&return=json&timestamp=1409887191
```

Response example:

```
{
  "2014-08-01": {"deliver": {"cost": "0.500", "parts": "1"}, "2014-08-06": {"deliver": {"cost": "0.600", "parts": "1"}, "not_deliver": {"cost": "0.600", "parts": "1"}, "2014-08-07": {"deliver": {"cost": "1.200", "parts": "2"}, "not_deliver": {"cost": "1.800", "parts": "3"}, "2014-08-08": {"not_deliver": {"cost": "0.700", "parts": "1"}, "deliver": {"cost": "0.600", "parts": "1"}, "2014-08-09": {"not_deliver": {"cost": "506.800", "parts": "768"}, "deliver": {"cost": "858.700", "parts": "1304"}, "expired": {"cost": "80.500", "parts": "122"}, "2014-08-11": {"not_deliver": {"cost": "32.700", "parts": "50"}, "expired": {"cost": "7.900", "parts": "12"}, "deliver": {"cost": "57.000", "parts": "86"}, "2014-08-13": {"expired": {"cost": "0.600", "parts": "1"}, "2014-08-14": {"deliver": {"cost": "8080.850", "parts": "18071"}, "not_deliver": {"cost": "4695.000", "parts": "10546"}, "expired": {"cost": "992.250", "parts": "2217"}, "2014-08-15": {"deliver": {"cost": "1738.300", "parts": "3909"}, "expired": {"cost": "194.300", "parts": "436"}, "not_deliver": {"cost": "1057.700", "parts": "2380"}, "2014-08-19": {"expired": {"cost": "2564.350", "parts": "5703"}, "not_deliver": {"cost": "2565.800", "parts": "5681"}, "deliver": {"cost": "4248.100", "parts": "9416"}, "2014-08-25": {"not_deliver": {"cost": "621.250", "parts": "1345"}, "deliver": {"cost": "978.550", "parts": "2116"}, "expired": {"cost": "109.900", "parts": "237"}, "2014-08-26": {"deliver": {"cost": "10.500", "parts": "21"}, "not_deliver": {"cost": "4.500", "parts": "9"}, "expired": {"cost": "1.000", "parts": "2"}, "2014-08-27": {"deliver": {"cost": "1339.950", "parts": "2836"}, "expired": {"cost": "160.400", "parts": "340"}, "not_deliver": {"cost": "836.050", "parts": "1769"}, "2014-08-28": {"expired": {"cost": "357.000", "parts": "714"}, "deliver": {"cost": "2901.500", "parts": "5803"}, "not_deliver": {"cost": "1796.000", "parts": "3592"}, "2014-08-29": {"not_deliver": {"cost": "0.500", "parts": "1"}}}
```

Request example:

https://go.intistele.com/external/get/stat_by_month.php?login=testuser&signature=809673402e973567ef892651a9714bf9&month=2014-08&return=xml×tamp=1409887191

Response example:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
<statiscics>
<date date="2014-08-01" deliver_cost="0.500" deliver_parts="1" />
<date date="2014-08-06" deliver_cost="0.600" deliver_parts="1" not_deliver_cost="0.600" not_deliver_parts="1" />
<date date="2014-08-07" deliver_cost="1.200" deliver_parts="2" not_deliver_cost="1.800" not_deliver_parts="3" />
<date date="2014-08-08" not_deliver_cost="0.700" not_deliver_parts="1" deliver_cost="0.600" deliver_parts="1" />
<date date="2014-08-09" not_deliver_cost="506.800" not_deliver_parts="768" deliver_cost="858.700" deliver_parts="1304" expired_cost="80.500" expired_parts="122" />
<date date="2014-08-11" not_deliver_cost="32.700" not_deliver_parts="50" expired_cost="7.900" expired_parts="12" deliver_cost="57.000" deliver_parts="86" />
<date date="2014-08-13" expired_cost="0.600" expired_parts="1" />
<date date="2014-08-14" deliver_cost="8080.850" deliver_parts="18071" not_deliver_cost="4695.000" not_deliver_parts="10546" expired_cost="992.250" expired_parts="2217" />
<date date="2014-08-15" deliver_cost="1738.300" deliver_parts="3909" expired_cost="194.300" expired_parts="436" not_deliver_cost="1057.700" not_deliver_parts="2380" />
<date date="2014-08-19" expired_cost="2564.350" expired_parts="5703" not_deliver_cost="2565.800" not_deliver_parts="5681" deliver_cost="4248.100" deliver_parts="9416" />
<date date="2014-08-25" not_deliver_cost="621.250" not_deliver_parts="1345" deliver_cost="978.550" deliver_parts="2116" expired_cost="109.900" expired_parts="237" />
<date date="2014-08-26" deliver_cost="10.500" deliver_parts="21" not_deliver_cost="4.500" not_deliver_parts="9" expired_cost="1.000" expired_parts="2" />
<date date="2014-08-27" deliver_cost="1339.950" deliver_parts="2836" expired_cost="160.400" expired_parts="340" not_deliver_cost="836.050" not_deliver_parts="1769" />
<date date="2014-08-28" expired_cost="357.000" expired_parts="714" deliver_cost="2901.500" deliver_parts="5803" not_deliver_cost="1796.000" not_deliver_parts="3592" />
<date date="2014-08-29" not_deliver_cost="0.500" not_deliver_parts="1" />
</statiscics>
</response>
```

14. HLR request

HLR request

Server address for requests: <https://go.intistele.com/external/get/hlr.php>

It is necessary to specify in the request four obligatory parameters **login**, **phone**, **signature** and **timestamp**

login - Your login

signature - signature

phone - one or several numbers separated by commas, but no more than 100 numbers in the request

timestamp - UTC Timestamp

Request example:

```
https://go.intistele.com/external/get/hlr.php?login=testuser&phone=17076295568&signature=5c50203e2e9edac49394b019e2be673e&timestamp=1480267368
```

Request example:

```
https://go.intistele.com/external/get/hlr.php?login=testuser&phone=17076295568&signature=5c50203e2e9edac49394b019e2be673e&timestamp=1480267368&return=json
```

Request example:

```
https://go.intistele.com/external/get/hlr.php?login=testuser&phone=17076295568&signature=5c50203e2e9edac49394b019e2be673e&timestamp=1480267368&return=xml
```

15. Statistics of HLR requests

Statistics of HLR requests

Server address for requests: https://go.intistele.com/external/get/hlr_stat.php

It is necessary to specify in the request five obligatory parameters **login**, **from**, **to**, **signature** and **timestamp**

login - Your login

signature - signature

from - date of start in the format YYYY-MM-DD

to - date of end in the format YYYY-MM-DD

timestamp - UTC Timestamp

Request example:

```
https://go.intistele.com/external/get/hlr_stat.php?login=testuser&from=2014-04-06&to=2014-05-06&signature=b27f321d0b50d914ebbd01f754fe7af7&timestamp=1409887191
```

Request example:

```
https://go.intistele.com/external/get/hlr_stat.php?login=testuser&from=2014-04-06&to=2014-05-06&signature=b27f321d0b50d914ebbd01f754fe7af7&timestamp=1409887191&return=json
```

Request example:

```
https://go.intistele.com/external/get/hlr_stat.php?login=testuser&from=2014-04-06&to=2014-05-06&signature=b27f321d0b50d914ebbd01f754fe7af7&timestamp=1409887191&return=xml
```

16. Mobile operator query

Mobile operator query

Server address for requests: <https://go.intistele.com/external/get/operator.php>

It is necessary to specify in the request four obligatory parameters **login**, **signature**, **timestamp** and **phone**

login - Your login

signature - signature

phone - Phone number

text - Text of SMS message

timestamp - UTC Timestamp

Request example:

```
https://go.intistele.com/external/get/operator.php?login=testuser&signature=887db6cdd1569557a6bcb8302536e725&timestamp=1480267421&phone=17076295568
```

There is a five optional parameter **return** that can be one of two values: json, xml

Request example:

```
https://go.intistele.com/external/get/operator.php?login=testuser&signature=93a3807d57e850f3c15915e45fe1d73d&timestamp=1480267421&return=json&phone=17076295568
```

Response example:

```
{"currency": "USD", "error": 0, "mcc": "000", "mnc": "00", "ok": true, "operator": "AT&T", "phone": "1XXXXXXXXXX", "ported": 0, "price": 0.65, "regionCode": 0, "timeZone": 0}
```

17. Request for incoming SMS

Request for incoming SMS

Server address for requests: <https://go.intistele.com/external/get/incoming.php>

It is necessary to specify in the request four or five obligatory parameters **login**, **signature**, **date** OR (**from** AND **to**), **timestamp**

login - Your login

signature - signature

date - date in the format YYYY-MM-DD

from - date of start in the format YYYY-MM-DD HH:II:SS (Example: 2014-05-01 14:06:00)

to - date of end in the format YYYY-MM-DD HH:II:SS (Example: 2014-05-30 23:59:59)

timestamp - UTC Timestamp

(You can use «date» parameter OR «from» AND «to» parameters all together, if three of them are used simultaneously ,then the system will automatically select «date» parameter by default)

Request example:

```
https://go.intistele.com/external/get/incoming.php?login=testuser&signature=92f571dfaf06c9adc6e3eb3accd95681&timestamp=1480267440&date=2016-11-27
```

There is a optional parameter **return** that can be one of two values: json, xml

Request example:

```
https://go.intistele.com/external/get/incoming.php?login=testuser&signature=92f571dfaf06c9adc6e3eb3accd95681&timestamp=1480267440&return=json&date=2016-11-27
```

Response example:

```
{{"5597" : {"date":"2014-10-27 05:47:24", "sender":"17076295568", "prefix":"51632", "text":"51632 TEST"}}
```

Request example:

```
https://go.intistele.com/external/get/incoming.php?login=testuser&signature=92f571dfaf06c9adc6e3eb3accd95681&timestamp=1480267440&return=xml&date=2016-11-27
```

Response example:

```
<?xml version="1.0" encoding="utf-8"?>
  <response>
    <sms
      id_sms="5597"
      date="2014-10-27 05:47:24"
      sender="17076295568"
      prefix="51632"
      text="51632 TEST"
    />
```

```
</response>
```


18. Request for prices

Prices request

Server address for requests: <https://go.intistele.com/external/get/prices.php>

It is necessary to specify in the request three obligatory parameters **login**, **signature** and **timestamp**

login - Your login

signature - signature

timestamp - UTC Timestamp

Request example:

```
https://go.intistele.com/external/get/prices.php?login=testuser&signature=32c64ef7da3f7a9d2239459fe076f13d&timestamp=1480267487
```

Response example:

```
{"25099": {"NETWORK_NAME": "BEELINE", "COUNTRY": "RUSSIAN FEDERATION", "PRICE": "0.65", "CURRENCY": "RUB"}, "25001": {"NETWORK_NAME": "MTS", "COUNTRY": "RUSSIAN FEDERATION", "PRICE": "0.65", "CURRENCY": "RUB"}, "25002": {"NETWORK_NAME": "MEGAFON", "COUNTRY": "RUSSIAN FEDERATION", "PRICE": "0.65", "CURRENCY": "RUB"}, "25020": {"NETWORK_NAME": "TELE2", "COUNTRY": "RUSSIAN FEDERATION", "PRICE": "0.65", "CURRENCY": "RUB"}}
```

19. Error codes

Error codes

- 000 - Service unavailable
- 1 - Signature not specified
- 2 - Login not specified
- 3 - Text not specified
- 4 - Phone number not specified
- 5 - Sender not specified
- 6 - Invalid signature
- 7 - Invalid login
- 8 - Invalid sender name
- 9 - Sender name not registered
- 10 - Sender name not approved
- 11 - There are forbidden words in the text
- 12 - Error in SMS sending
- 13 - Phone number is in the stop list. SMS sending to this number is forbidden.
- 14 - There are more than 50 numbers in the request
- 15 - List not specified
- 16 - Invalid phone number
- 17 - SMS ID not specified
- 18 - Status not obtained
- 19 - Empty response
- 20 - The number already exists
- 21 - No name
- 22 - Template already exists
- 23 - Month not specifies (Format: YYYY-MM)
- 24 - Timestamp not specified
- 25 - Error in access to the list
- 26 - There are no numbers in the list
- 27 - No valid numbers
- 28 - Date of start not specified (Format: YYYY-MM-DD)
- 29 - Date of end not specified (Format: YYYY-MM-DD)
- 30 - No date (format: YYYY-MM-DD)
- 31 - Closing direction to the user
- 32 - Not enough money